




ITEM	DESCRIPTION	MATERIAL
1	BODY - HALF	300 Series SS
2	SEAT INSERT SEAL	EPDM
3	SEAT INSERT	300 Series SS
4	SEAT SEAL	FEP Encapsulated Viton
5	RAM-TYPE PLUG	300 Series SS
6	BODY SEAL	EPDM
7	OPERATING SPRING	300 Series SS
8	THERMAL ACTUATOR	Brass
9	ACTUATOR CARRIER	Brass
10	BODY - HALF	300 Series SS



NOTES:

1. Cv: 1.5.
2. PORT SIZE: C.
3. WEIGHT: 0.9 Lb (0.4 Kg).
4. MAXIMUM OPERATING PRESSURE: 200 PSIG (13.8 BAR).
5. MAXIMUM TEMPERATURE: 300°F (149°C).
6. REVERSE FLOW OPTION IS RATED 150 PSIG (10.33 BAR).
7. FULL OPEN TEMPERATURE, "XXX", IS 105°F. OPTIONAL FULL OPEN TEMPERATURES, "XXX": 95°F, 100°F, 110°F, AND 115°F.
8. A #20 MESH STRAINER IS RECOMMENDED.

FLUID SENSING
(REVERSE FLOW) →
NOTE 6

COMPONENT	SCALD PROTECTION VALVE
-----------	------------------------

ThermOmegaTech
ThermOmegaTech, Inc.
353 Ivyland Road
Warminster, PA 18974-2205, USA
Ph: 215-798-5978

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. ThermOmegaTech makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

This drawing is the property of ThermOmegaTech. It contains confidential, proprietary information that is ThermOmegaTech property. Do not disclose to or duplicate for others except as authorized by ThermOmegaTech.

SCALE	NTS
-------	-----

124-702100-XXX
1/2" HAT/SP-XXX-C-RF-E (Fluid Sensing)

UNIT	INCH [MM]
SHEET	1 of 1