



**NOTES:**

1. Cv: 2.0.
2. PORT SIZE: D.
3. WEIGHT: 1.4 Lb (0.6 Kg).
4. MAXIMUM OPERATING PRESSURE: 200 PSIG (13.8 BAR).
5. MAXIMUM TEMPERATURE: 300°F (149°C).
6. FULL OPEN TEMPERATURE, "XXX", IS 105°F. OPTIONAL FULL OPEN TEMPERATURES, "XXX": 95°F, 100°F, 110°F, AND 115°F.
7. SS = 303 STAINLESS STEEL.
8. A #20 MESH STRAINER IS RECOMMENDED.

<b>COMPONENT</b>		<b>SCALD PROTECTION VALVE</b>	
<b>125-512100-XXX</b>		<b>UNIT</b>	INCH [MM]
		<b>SHEET</b>	1 of 1
<b>SCALE</b>	NTS	3/4" HAT/SP-XXX-D-SS-E (Ambient Sensing)	

**ThermOmegaTech**  
 ThermOmegaTech, Inc.  
 353 Ivyland Road  
 Warminster, PA 18974-2205, USA  
 Ph: 215-798-5978

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. ThermOmegaTech makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

This drawing is the property of ThermOmegaTech. It contains confidential, proprietary information that is ThermOmegaTech property. Do not disclose to or duplicate for others except as authorized by ThermOmegaTech.