



NOTES:

1. DIMENSIONAL TOLERANCES: ±1/2".
2. RECOMMENDED WATER PRESSURE: 55 PSI (3.79 BAR) MIN. 90 PSI (6.21 BAR) MAX.
3. RECOMMENDED STEAM PRESSURE: 45 PSI TO 60 PSI (3.10 BAR TO 4.14 BAR).
4. MAXIMUM STEAM TEMPERATURE: 350° F (177° C).
5. CONFORMS TO OSHA AND ANSI RECOMMENDATIONS.
6. DESIGNED TO MEET ASSE 1071 REQUIREMENTS.

SPECIFICATIONS:

1. COLD WATER BYPASS FLOW RATE 24 GPM @ 25 PSI PRESSURE DROP.
2. WATER INLET & OUTLET PIPE SIZE 1 1/4" NPT (F).
3. STEAM SUPPLY & DRAIN PIPE SIZE 1" NPT (F).
4. PRESSURE DROP WATER INLET 25 PSI @ 25 GPM.

COMPONENT		THERM-O-MIX STATION	
387-112100-003		UNIT	
		INCH [MM]	
THERM-O-MIX STATION, BPHE (45-60 PSIG STEAM)		SHEET	
			1 of 1

ThermOmegaTech
 ThermOmegaTech, Inc.
 353 Ivyland Road
 Warminster, PA 18974-2205, USA
 Ph: 215-798-5978

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. ThermOmegaTech makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

This drawing is the property of ThermOmegaTech. It contains confidential, proprietary information that is ThermOmegaTech property. Do not disclose to or duplicate for others except as authorized by ThermOmegaTech.

SCALE NTS

4

3

2

1

B

B

A

A

4

3

2

1