

NOTES:

Α

2.5 [64]

- 1. WEIGHT: 6.8 Lbs (3.1 Kg).
- 2. Cv: OPEN: 3.3, CLOSED: 0.2, DESIGN: 1.57.
- 3. MAXIMUM WORKING PRESSURE: 200 PSIG (14 BAR).
- 4. MAXIMUM WORKING TEMPERATURE: 250°F (121°C).
- 5. XXX REFERS TO THE DESIRED CLOSING TEMPERÁTURE.
- 6. ALL COMPONENTS ARE NSF/ANSI/CAN 61 OR 372 CERTIFIED.

• ThermOmegaTech

ThermOmegaTech, Inc. 353 Ivyland Road Warminster, PA 18974-2205, USA Ph: 215-798-5978 are provided for reference and evaluation purposes only, and is subject to change without notice. ThermOmegaTech makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications.

You are solely responsible for the use of the file, information or specifications.

This file and any associated information and specifications

14.3

[363]

This drawing is the property of ThermOmegaTech. It contains confidential, proprietary information that is ThermOmegaTech property. Do not disclose to or duplicate for others except as authorized by ThermOmegaTech.

2x 1" FNPT

SCALE NTS

COMPONENT CircuitSolver® Union Assembly with Strainer and Webstone Drain Valve

UNIT

[81]

CSUAS-1-XXX-CV1-WDV

1" - CSUAS AND WEBSTONE DRAIN VALVE

1

INCH [MM]

1 of 1

4 2

А